



A comparative analysis of Fuzzy AHP and Fuzzy VIKOR methods for prioritization of the risk criteria of an autonomous vehicle system

Marmar Mehrparvar^{a*}, Jüri Majak^{a,b} and Kristo Karjust^a

^a Department of Mechanical and Industrial Engineering, Tallinn University of Technology, Ehitajate tee 5, 19086 Tallinn, Estonia

^b FinEst Centre for Smart Cities, Tallinn University of Technology, Ehitajate tee 5, 19086 Tallinn, Estonia

Received 7 November 2023, accepted 18 December 2023, available online 21 March 2024

© 2024 Authors. This is an Open Access article distributed under the terms and conditions of the Creative Commons Attribution 4.0 International License CC BY 4.0 (<http://creativecommons.org/licenses/by/4.0>).

Abstract. In the current study, two widely used multi-criteria decision-making methods, the Fuzzy analytic hierarchy process (AHP) and the Fuzzy VIKOR method, have been implemented to prioritize the criteria of a multi-criteria decision-making problem. Herein, the case study is an autonomous vehicle, the TalTech iseAuto AV shuttle, developed at TalTech University. The criteria of the present problem are evaluated by experts, and after forming the pairwise matrices, these matrices are aggregated by the max-min method with the arithmetic mean. Subsequently, in the case of Fuzzy AHP, by calculating the weights and normalizing them, the relative importance of each criterion is obtained, which leads to the ranking of the criteria. Moreover, in the case of the Fuzzy VIKOR method, the aggregated pairwise matrix is weighted and normalized. The ranking obtained from both methods is presented and compared. The advantages and disadvantages of the multi-criteria decision-making methods Fuzzy AHP and VIKOR, featured for risk analysis of the autonomous vehicle systems, are discussed.

Keywords: multi-criteria decision-making problem, Fuzzy analytic hierarchy process (AHP), Fuzzy VIKOR method, prioritization of criteria, autonomous vehicle (AV).

INTRODUCTION

The importance of studying multi-criteria decision-making (MCDM) problems cannot be underestimated in our increasingly complex world of decision-making. In the context of decision processes, such problems arise due to simultaneous consideration of multiple, often conflicting criteria. For a systematic evaluation of options, MCDM methods provide an approach where the diverse qualitative and numerical aspects are considered. Their relevance extends to a wide variety of fields, from business and engineering to environmental management and health care. These criteria are often not of equal importance, and the performance of alternatives is quite different. Formal methods are necessary to provide for a structured decision-making process. A number of techniques have been introduced for handling multiple criteria, for instance, evolutionary optimization [1–4], the analytic hierarchy process (AHP), the technique for order of preference by similarity to ideal solution (TOPSIS), and the *vlsekriterijumska optimizacija i kompromisno resenje* (multi-criteria optimization and compromise solution – VIKOR) method [5–9]. In order to ascertain the efficacy of two well-known MCDM techniques in terms of ranking these important criteria in the context of autonomous vehicle systems, this paper compares the AHP and the VIKOR methods.

* Corresponding author, marmar.mehrparvar@taltech.ee

Fuzzy sets, first introduced by Zadeh [10], have been widely used in conjunction with Fuzzy AHP, which was introduced by Saaty [11], to assess complicated multi-criteria situations. For example, Kaganski et al. [12] assigned priority indexes to metrics using Fuzzy AHP based on the SMARTER (simple multi-attribute rating technique exploiting ranks) criterion. In addition, to improve the management of product data or lifecycle management, Paavel et al. [13] used Fuzzy AHP.

However, VIKOR, which was introduced in 1998 by Opricovic [14], is notable for its capacity to provide solutions that strike a compromise when faced with multi-criteria decision-making challenges. Since then, many studies have implemented this method in many areas, such as the energy sector [15], health [16], education [17,18], manufacturing, and industry [19,20]. The purpose of this comparison study is to shed light on whether these methods are appropriate for handling the difficulties connected to determining how criteria should be prioritized in the context of autonomous vehicle systems. Over the years, many investigations have been conducted to compare and review the VIKOR method with other methods [21–24].

The autonomous vehicle known as the AV shuttle, which was developed by Astrov et al. [25], Sell and Petritsenko [26], and Rassõlkin et al. [27], serves as the case study for this investigation. Pikner et al. [28,29] provide a detailed introduction to the criteria and risks of such a vehicle. In particular, [29] examines the risk analysis of this model by combining Fuzzy AHP with TOPSIS.

In the current study, the Fuzzy AHP and VIKOR methods are configured/tuned for risk evaluation of the autonomous vehicle systems. In the first step, the criteria are introduced and linguistically evaluated by experts, which leads to the formation of pairwise matrices. These matrices are aggregated by the max-min method with the arithmetic mean, and after obtaining the final pairwise matrix, two different paths are followed according to the two multi-criteria decision-making methods.

In the case of the Fuzzy AHP method, by implementing the arithmetic mean as the aggregation method, the fuzzy weights are calculated and, after normalization, can be sorted to obtain the ranking of criteria.

In the case of the Fuzzy VIKOR method, a linear normalization is used to stabilize the problem, and then the utility measures are calculated. Consequently, the VIKOR scores are calculated and sorted to obtain the rank of each criterion.

FORMULATION DEVELOPMENT FOR THE MCDM PROBLEM

As mentioned before, the current study is an investigation in continuation of a previous work by Pikner et al. [29]; in that work the criteria for the mobile robot were introduced, which will be considered here. There are seven criteria for the current problem: mission computer and AI performance (C1), cybersecurity (C2), malfunction of an AV mechanical component (C3), sensor system (C4), communication link (C5), weather factors (C6), and low-level cyber-physical system performance (C7).

After establishing the criteria involved in the system, the criteria are linguistically evaluated by experts, and the relative importance of the criteria in terms of linguistics variables from the least important to the most important is equated to the numerical values from 1 to 9, crisp AHP scale. Then, the scales are translated into triangular fuzzy numbers (TFN) [12]. Thus, each expert evaluates the importance of the criteria against each other and forms a pairwise comparison matrix linguistically, which then is transformed according to the numerical values.

The experts can indicate that a criterion is equally preferred, or equally to moderately preferred, or moderately preferred, or moderately to strongly preferred, or strongly preferred, or strongly to very strongly preferred, or very strongly preferred, or very strongly to extremely preferred, or extremely preferred to another criterion.

Since each expert could have a unique opinion regarding the importance of the criteria, these pairwise matrices are going to be different, and in order to form a final pairwise matrix, an appropriate aggregation method is utilized. The upper and lower bounds of the aggregated TFN, h and l , are chosen by the max-min method, and the middle-value m is calculated by the arithmetic mean. The aggregated fuzzy number $X_{ij} = (l_{ij}, m_{ij}, h_{ij})$, the relative importance of criterion X_i over criterion X_j , can be calculated by the max-min method with the arithmetic mean in Eq. (1):

$$\begin{aligned}
 h_{ij} &= \max_{t=1,2,\dots,q} (h_{ij}^{(t)}), \\
 m_{ij} &= \frac{1}{q} \sum_{t=1}^q m_{ij}^{(t)}, \\
 l_{ij} &= \min_{t=1,2,\dots,q} (l_{ij}^{(t)}),
 \end{aligned} \tag{1}$$




Fig. 1. Overview of the Fuzzy AHP and Fuzzy VIKOR methods.

where q is the number of experts. First, the final pairwise comparison matrix of criteria is determined. Next, two various methods for solving the MCDM problem are implemented to rank the criteria. Below, the Fuzzy AHP and the Fuzzy VIKOR methods are explored. Figure 1 shows the process of both methods in one glance. As can be observed, both methods' processes are the same until the calculation of the aggregated pairwise matrix, after which the differentiation of these methods begins.

The analytic hierarchy process (AHP)

AHP, as described before, is a systematic and structured way of making decisions by breaking down the problem into pairwise comparisons and then aggregating the results [5]. After obtaining the final pairwise matrix in Eq. (2), the weights are calculated by utilizing the arithmetic mean as the aggregation method, as shown in Eq. (3).

$$C = \begin{bmatrix} x_{11} & x_{12} & \cdots & x_{1n} \\ x_{21} & x_{22} & \cdots & x_{2n} \\ \vdots & \vdots & \vdots & \cdots \\ x_{m1} & x_{m2} & \vdots & x_{mn} \end{bmatrix}, \quad i = 1, 2, \dots, m; j = 1, 2, \dots, n. \tag{2}$$

$$x_i = \frac{1}{n}(x_{i1} \oplus x_{i2} \oplus \dots \oplus x_{in}), \quad (3)$$

which is normalized as such:

$$w_i = \frac{x_i}{\sum_{j=1}^n x_j}. \quad (4)$$

To conclude, the centroid method is used to defuzzify the fuzzy weight, and the crisp weight is calculated as such:

$$w = \frac{l + m + h}{3}. \quad (5)$$

In this method, the crisp weights of the respective criteria are ranked, with the highest weight value corresponding to the most important criteria.

The VIKOR method

As previously stated, this method determines the compromise solution and the best solution from a set of alternatives. The compromise solution will be presented by comparing the degree of closeness to the ideal alternative, and each alternative can be evaluated by each criterion function [21]. A systematic approach of the Fuzzy VIKOR method for multi-criteria in a fuzziness environment is given in this section, based on [6,8,16].

At first, the fuzzy pairwise matrix in Eq. (2) needs to get normalized in order to ensure that all criteria are standard and comparable to each other. Here, linear normalization is utilized for stabilisation, which is provided by R_{ij} as follows:

$$R_{ij} = \left(\frac{x_{ij}^* - x_{ij}}{x_{ij}^* - x_{ij}^-} \right), \quad (6)$$

where R_{ij} is the normalized score for the alternative i of the j th criteria, x_{ij} is the value of the j th criteria for the alternative i , and the best value of the j th criteria is x_{ij}^* and the worst value x_{ij}^- .

The utility measures will be calculated at this stage:

$$\begin{aligned} S_i &= \sum_{j=1}^n w_j R_{ij}, \\ R_i &= \max_j [w_j R_{ij}], \end{aligned} \quad (7)$$

where w_j is the weight of the j th criteria, and S_i and R_i are the alternative distance values to positive and negative ideal solutions, respectively. Hence, the VIKOR score Q_i is obtained by

$$Q_i = v \left(\frac{S_i - S^-}{S^+ - S^-} \right) + (1 - v) \left(\frac{R_i - R^-}{R^+ - R^-} \right), \quad (8)$$

where

$$\begin{aligned} S^+ &= \max_i S_i, & S^- &= \min_i S_i, \\ R^+ &= \max_i R_i, & R^- &= \min_i R_i. \end{aligned} \quad (9)$$

Also, the parameter ν is the strategy of the maximum utility, which is a value between 0 to 1. In this paper, this parameter is chosen to be 0.5.

Finally, the defuzzification is done for parameters S , R , and Q , and ranking is done based on the obtained value for Q . The smaller the VIKOR score value, the better the alternative solution.

NUMERICAL RESULTS AND DISCUSSION

In this section, the final results of the ranking of the criteria are presented. For the system with seven criteria mentioned above, six experts give their evaluations of the criteria, which are then transformed into a pairwise comparison matrix [29]. Then the linguistic values are transferred to TFN according to [28]. The aggregated evaluation matrix is obtained by the max-min method with the arithmetic mean. First, to study the results of the Fuzzy AHP method, the fuzzy weights and crisp weights are calculated, and the criteria are ranked from the most important to the least important. The results are validated with results from the literature (Table 1).

As can be observed, the results show a good agreement with each other. For this case study, the final values of S , R , and Q are presented in Table 2. In the Fuzzy VIKOR method, the ranking of the VIKOR score is done so that the smallest value refers to the most important criteria and the largest value to the least important criteria.

It is worth mentioning that these results are for $\nu = 0.5$, and, as mentioned before, this value is chosen according to the literature. In the case of higher values, the value of Q will tend toward a majority agreement and, consequently, when it has lower values, Q will tend toward a majority negative attitude [24].

As can be seen in Table 2, the parameter values, both fuzzy and crisp, can get extremely close, and extra care is needed to ensure the accuracy of final values and ranking.

Table 1. Weights and ranking of criteria based on Fuzzy AHP and the results from [29]

Criteria	Fuzzy AHP			[29]		
	Aggregated fuzzy comparison value	Crisp weights	Final rank	Aggregated fuzzy comparison value	Crisp weights	Final rank
C1	(0.37, 1.03, 2.64)	0.08940	7	(0.51, 0.60, 0.71)	0.076	6
C2	(0.39, 1.99, 5.14)	0.14225	4	(0.86, 1.07, 1.34)	0.137	4
C3	(0.42, 2.21, 5.29)	0.15139	3	(0.98, 1.19, 1.46)	0.151	3
C4	(0.94, 3.07, 6.57)	0.23719	1	(1.83, 2.17, 2.50)	0.268	1
C5	(0.28, 0.99, 3.86)	0.09187	6	(0.44, 0.52, 0.65)	0.067	7
C6	(0.50, 0.99, 2.29)	0.09726	5	(0.56, 0.64, 0.73)	0.079	5
C7	(0.56, 2.74, 6.43)	0.19065	2	(1.49, 1.81, 2.09)	0.223	2

Table 2. The results of the Fuzzy VIKOR method and final ranking

Criteria	Fuzzy value S	Fuzzy value R	Fuzzy value Q	Crisp value Q	Final rank
C1	(0.80, 0.77, 0.62)	(0.36, 0.26, 0.23)	(0.76, 0.79, 0.78)	0.77739	6
C2	(0.78, 0.75, 0.60)	(0.35, 0.26, 0.23)	(0.71, 0.72, 0.76)	0.73010	4
C3	(0.70, 0.78, 0.36)	(0.34, 0.26, 0.23)	(0.34, 0.81, 0.50)	0.55151	3
C4	(0.77, 0.65, 0.47)	(0.34, 0.26, 0.20)	(0.55, 0.04, 0.12)	0.23855	1
C5	(0.92, 0.83, 0.64)	(0.36, 0.26, 0.23)	(1.00, 0.90, 0.79)	0.90162	7
C6	(0.75, 0.88, 0.83)	(0.36, 0.26, 0.23)	(0.64, 0.65, 1.00)	0.76163	5
C7	(0.68, 0.63, 0.77)	(0.31, 0.26, 0.22)	(0.00, 0.50, 0.91)	0.46919	2

Table 3. Comparison of the results obtained from Fuzzy AHP and Fuzzy VIKOR

Criteria	Fuzzy AHP			Fuzzy VIKOR		
	Aggregated fuzzy comparison value	Crisp weights	Final rank	Fuzzy value \bar{Q}	Crisp value \bar{Q}	Final rank
C1	(0.37, 1.03, 2.64)	0.08940	7	(0.76, 0.79, 0.78)	0.77739	6
C2	(0.39, 1.99, 5.14)	0.14225	4	(0.71, 0.72, 0.76)	0.73010	4
C3	(0.42, 2.21, 5.29)	0.15139	3	(0.34, 0.81, 0.50)	0.55151	3
C4	(0.94, 3.07, 6.57)	0.23719	1	(0.55, 0.04, 0.12)	0.23855	1
C5	(0.28, 0.99, 3.86)	0.09187	6	(1.00, 0.90, 0.79)	0.90162	7
C6	(0.50, 0.99, 2.29)	0.09726	5	(0.64, 0.65, 1.00)	0.76163	5
C7	(0.56, 2.74, 6.43)	0.19065	2	(0.00, 0.50, 0.91)	0.46919	2

Finally, the rankings obtained from both methods, Fuzzy AHP and Fuzzy VIKOR, are compared, and they show a good agreement (Table 3). However, it should be kept in mind that each of these methods has its advantages; for instance, the Fuzzy AHP method is straightforward and does not require an additional tool for criteria prioritization. Likewise, Fuzzy VIKOR provides a ranking procedure for positive attributes and negative attributes and ensures the balance between them.

CONCLUSIONS

The current investigation, in continuation of previous work, develops a formulation to solve a multi-criteria decision-making problem. The current case study is an AV shuttle system that has seven criteria; these criteria are linguistically evaluated by six experts. After forming the pairwise matrices, the max-min method with the arithmetic mean has been utilized to aggregate them to form a singular pairwise matrix, comparing the importance of the criteria to each other. In the case of Fuzzy AHP, based on the aggregated matrix, the fuzzy weights are calculated and defuzzified to obtain crisp weights. The ranking of the criteria is performed based on crisp weights. In the case of Fuzzy VIKOR, the linearization has been carried out, and the values of the utility measures and, subsequently, the VIKOR scores are calculated. The results of the Fuzzy AHP method are in accordance with the results of the previous study, and the results for both methods are compared, which exhibit a good agreement. The Fuzzy AHP method is beneficial in the case of a certain degree of inconsistency during pairwise comparisons and provides a robust way to transform decision-makers' judgments into numerical results [9]. However, in the Fuzzy VIKOR method, compromise in conflict resolution may occur [21].

ACKNOWLEDGMENTS

This research has received funding from three grants: AI & Robotics Estonia – EDIH (project No.101083677); Master of Science in Smart, Secure and Interconnected Systems (MERIT) – development of a new pan-European educational ecosystem for training of digital specialists (project No. VEU22048, DIGITAL-2021-SKILLS-01); the European Union's Horizon 2020 Research and Innovation Programme, under grant agreement No. 856602; and the European Regional Development Fund, co-funded by the Estonian Ministry of Education and Research, under grant agreement No. 2014-2020.4.01.20-0289. The publication costs of this article were partially covered by the Estonian Academy of Sciences.

REFERENCES

1. Jaanuska, L. and Hein, H. Delamination quantification by Haar wavelets and machine learning. *Mech. Compos. Mater.*, 2022, **58**, 249–260. <https://doi.org/10.1007/s11029-022-10025-2>
2. Aydin, L., Artem, H. S. and Deveci, H. A. Single- and multiobjective optimizations of dimensionally stable composites using genetic algorithms. *Mech. Compos. Mater.*, 2021, **57**, 321–336. <https://doi.org/10.1007/s11029-021-09957-y>
3. Barkanov, E., Akishin, P., Namsone, E., Auzins, J. and Morozovs, A. Optimization of pultrusion processes for an industrial application. *Mech. Compos. Mater.*, 2021, **56**, 697–712. <https://doi.org/10.1007/s11029-021-09916-7>
4. Kers, J., Majak, J., Goljandin, D., Gregor, A., Malmstein, M. and Vilsaar, K. Extremes of apparent and tap densities of recovered GFRP filler materials. *Compos. Struct.*, 2010, **92**(9), 2097–2101. <https://doi.org/10.1016/j.compstruct.2009.10.003>
5. Vinodh, S., Prasanna, M. and Hari Prakash, N. Integrated Fuzzy AHP–TOPSIS for selecting the best plastic recycling method: a case study. *Appl. Math. Model.*, 2014, **38**(19–20), 4662–4672. <https://doi.org/10.1016/j.apm.2014.03.007>
6. Bakioglu, G. and Atahan, A. O. AHP integrated TOPSIS and VIKOR methods with Pythagorean fuzzy sets to prioritize risks in self-driving vehicles. *Appl. Soft Comput.*, 2021, **99**, 106948. <https://doi.org/10.1016/j.asoc.2020.106948>
7. Kuo, R. J., Lee, L. Y. and Hu, T.-L. Developing a supplier selection system through integrating fuzzy AHP and fuzzy DEA: a case study on an auto lighting system company in Taiwan. *Prod. Plan. Control*, 2010, **21**(5), 468–484. <https://doi.org/10.1080/09537280903458348>
8. Yazdani, M. and Graeml, F. R. VIKOR and its applications: a state-of-the-art survey. *Int. J. Strateg. Decis. Sci.*, 2014, **5**(2), 56–83. <https://doi.org/10.4018/ijds.2014040105>
9. Afolayan, A. H., Ojokoh, B. A. and Adetunmbi, A. O. Performance analysis of fuzzy analytic hierarchy process multi-criteria decision support models for contractor selection. *Sci. Afr.*, 2020, **9**, e00471. <https://doi.org/10.1016/j.sciaf.2020.e00471>
10. Zadeh, L. A. Fuzzy sets. *Inf. Control*, 1965, **8**(3), 338–353. [https://doi.org/10.1016/S0019-9958\(65\)90241-X](https://doi.org/10.1016/S0019-9958(65)90241-X)
11. Saaty, T. L. *Analytic Hierarchy Process: Planning, Priority Setting, Resource Allocation*. McGraw-Hill International Book Co., New York, London, 1980.
12. Kaganski, S., Majak, J. and Karjust, K. Fuzzy AHP as a tool for prioritization of key performance indicators. *Procedia CIRP*, 2018, **72**, 1227–1232. <https://doi.org/10.1016/j.procir.2018.03.097>
13. Paavel, M., Karjust, K. and Majak, J. Development of a product lifecycle management model based on the fuzzy analytic hierarchy process. *Proc. Estonian Acad. Sci.*, 2017, **66**(3), 279–286. <https://doi.org/10.3176/proc.2017.3.05>
14. Opricovic, S. *Multicriteria optimization of civil engineering systems*. PhD thesis. Faculty of Civil Engineering, Belgrade, 1998.
15. Peleckis, K. Application of the Fuzzy VIKOR method to assess concentration and its effects on competition in the energy sector. *Energies*, 2022, **15**(4), 1349. <https://doi.org/10.3390/en15041349>
16. Afful-Dadzie, E., Nabareseh, S. and Oplatkova, Z. K. Fuzzy VIKOR approach: evaluating quality of internet health information. In *Proceedings of the 2014 Federated Conference on Computer Science and Information Systems (FedCSIS), Warsaw, Poland, 7–10 September 2014*. IEEE, 2014, 183–190.
17. Waas, D. V. and Suprpto, S. Combination of AHP method and VIKOR method for assessing Sunday school teacher. *IJCCS*, 2020, **14**(1). <https://doi.org/10.22146/ijccs.40533>
18. Musani, S. and Jemain, A. A. Ranking schools' academic performance using a Fuzzy VIKOR. *J. Phys: Conf. Ser.*, 2015, **622**, 612036. <https://doi.org/10.1088/1742-6596/622/1/012036>
19. Mat Rani, R. and Nadar, A. F. Supplier selection using Fuzzy AHP and Fuzzy Vikor for XYZ pharmaceutical manufacturing company. *EDUCATUM J. Sci. Math. Technol.*, 2020, **7**(1). <https://doi.org/10.37134/ejsmt.vol7.1.2.2020>
20. Anojkumar, L., Ilangkumaran, M. and Sasirekha, V. Comparative analysis of MCDM methods for pipe material selection in sugar industry. *Expert Syst. Appl.*, 2014, **41**(6), 2964–2980. <https://doi.org/10.1016/j.eswa.2013.10.028>
21. Opricovic, S. and Tzeng, G.-H. Extended VIKOR method in comparison with outranking methods. *Eur. J. Oper. Res.*, 2007, **178**(2), 514–529. <https://doi.org/10.1016/j.ejor.2006.01.020>
22. Papathanasiou, J. An example on the use and limitations of MCDA: the case of Fuzzy VIKOR. *Examples and Counterexamples*, 2021, **1**. <https://doi.org/10.1016/j.exco.2020.100001>
23. Ceballos, B., Lamata, M. T. and Pelta, D. A. A comparative analysis of multi-criteria decision-making methods. *Prog. Artif. Intell.*, 2016, **5**, 315–322. <https://doi.org/10.1007/s13748-016-0093-1>
24. Ju, Y. and Wang, A. Extension of VIKOR method for multi-criteria group decision making problem with linguistic information. *Appl. Math. Model.*, 2013, **37**(5), 3112–3125. <https://doi.org/10.1016/j.apm.2012.07.035>
25. Astrov, I., Udal, A., Pedai, A. and Sell, R. Simulink/MATLAB based comparison of neural and basic tracking control for an autonomous surface vessel for situation awareness applications. In *Proceedings of the IEEE Joint 19th International Symposium on Computational Intelligence and Informatics and 7th International Conference on Recent Achievements in Mechatronics, Automation, Computer Sciences and Robotics (CINTI-MACRo), Szeged, Hungary, 14–16 November 2019*. IEEE, 2019, 000105–000110. <https://doi.org/10.1109/CINTI-MACRo49179.2019.9105230>
26. Sell, R. and Petritsenko, A. Early design and simulation toolkit for mobile robot platforms. *Int. J. Prod. Dev.*, 2013, **18**(2). <https://doi.org/10.1504/IJPD.2013.053499>
27. Rassõlkin, A., Sell, R. and Leier, M. Development case study of the first Estonian self-driving car, ISEAUTO. *Electr. Control Commun. Eng.*, 2018, **14**(1). <https://doi.org/10.2478/ecce-2018-0009>

28. Pikner, H., Sell, R., Majak, J. and Karjust, K. Multi-layer cyber-physical control method for mobile robot safety systems. *Proc. Estonian Acad. Sci.*, 2021, **70**(4), 383–391. <https://doi.org/10.3176/proc.2021.4.03>
29. Pikner, H., Sell, R., Majak, J. and Karjust, K. Safety system assessment case study of autonomous vehicle shuttle. *Electronics*, 2022, **11**(7). <https://doi.org/10.3390/electronics11071162>

Fuzzy AHP ja Fuzzy VIKOR meetodite võrdlev analüüs autonoomse sõiduki süsteemiriskide prioriseerimisel

Marmar Mehrparvar, Jüri Majak ja Kristo Karjust

Multikriteeriaalse optimeerimisülesande lahendamiseks on uurimistöös rakendatud kahte multikriteeriaalset otsustusmeetodit: Fuzzy AHP ja Fuzzy VIKOR. Juhtumiuuringuks on valitud TalTechis arendatud autonoomse sõiduki süsteem. Ekspertid hindasid kriteeriume lingvistilise hindamise teel. Koostatud on paarikaupa võrdluste maatriksid ja rakendatud on max-min meetodit koos aritmeetilise keskmisega, et agregeerida üksikute ekspertide hinnangud. Lähtudes agregeeritud võrdlusmaatriksist, arvutatakse Fuzzy kolmikväärtustega kaalud, mis teisendatakse lõpptulemuse saamiseks üksikväärtusega kaaludeks. Kriteeriumid järjestatakse arvutatud kaalude põhjal. Fuzzy VIKOR meetodi korral lineariseeritakse ja arvutatakse VIKOR skoorid. Fuzzy AHP meetodi tulemused on kooskõlas eelnevalt saadud tulemustega. Uurimistöös on analüüsitud kahe meetodi rakendamisel saadud kriteeriumide järjestusi ning meetodite eeliseid ja kitsaskohti.